



NOTES:

1. TRAFFIC SIGNS TO BE PLACED ON 2" I.D. GALVANIZED STEEL PIPE (SCHEDULE 40)
2. ALL SIGNS SHALL LIST THE MONTH AND YEAR OF MANUFACTURE IN SMALL BLACK FONT ON LOWER RIGHT BORDER AREA
3. 3M DIAMOND GRADE DG3 3930 REFLECTIVE SHEETING OR APPROVED EQUAL, WITH 3M PREMIUM PROTECTIVE OVERLAY FILM 1160. ALL PARKING SIGNS MOUNTED ON LIGHT POLES TO BE DOUBLE SIDED WITH BANDING MOUNT, BAND TO BE BAND-IT PART NO. C905, 5/8" 304 STAINLESS STEEL. BUCKLE TO BE BAND-IT PART NO. C455, 5/8" EAR LOFT BUCKLE 316 STAINLESS STEEL OR APPROVED EQUAL. SIGN MOUNTING BRACKET TO BE SIMIFAST VCC286K, DOUBLE FACED CANTILEVER. USE TWO BUCKLES AND TWO BRACKETS PER SIGN
4. SIGN SADDLE, TAPCO NO. M2G-FUB OR APPROVED EQUAL TO BE USED FOR MOUNTING SINGLE FACED SIGNS TO THE FRONT OF LARGE DIAMETER POLES WITH BANDING STRAPS (E.G., A STREETLIGHT POLE)
5. TAPCO ALUMINUM L-BRACKET NO. M2G-2LBS-X UNTHREADED, RAW FINISH OR APPROVED EQUAL
6. TAPCO M2G-C2B SINGLE CLAMP-ON U BRACKET SET WITH MG2-BHX HEX HEAD BOLT
7. 3M DIAMOND GRADE DG3 REFLECTIVE R1-1, 30"x30" WITH 3M PREMIUM PROTECTIVE OVERLAY FILM 1160
8. PRIOR TO ORDERING STREET SIGNS, VERIFY WITH CITY ENGINEER THE EXACT LOCATION AND SIZE. MINIMUM 60" NEW / 48" EXISTING PEDESTRIAN ACCESS TO BE MAINTAINED WHERE FEASIBLE
9. SINGLE SHEET ALUMINUM SIGNS SHALL BE FABRICATED FROM .080 INCH THICK, 6061-T6, 5052-H38 ALUMINUM ALLOY. OR APPROVED EQUAL. SIGNS SHALL BE DEGREASED, DEBURRED, ETCHED AND FREE OF WHITE RUST.
10. SIGN SHAPES, HOLE PUNCHES AND CORNER RDII SHALL MEET CALIFORNIA DEPARTMENT OF TRANSPORTATION STANDARDS.
11. ALL NEW SIGNS SHALL HAVE 3M PREMIUM PROTECTIVE OVERLAY FILM (GRAFFITI FILM). SIGNS SHALL BE FABRICATED WITH 3M DIAMOND GRADE DG3 RETRO REFLECTIVE SHEETING BACKGROUND (ASTM TYPE IX SHEETING), AND SIGN DESIGN APPLIED WITH 3M ELECTRO CUT 1170 FILM OR PRINTED WITH LATEX INK.



City of San Bruno
Standard Detail

TRAFFIC SIGN FABRICATION & INSTALLATION		DATE: AUG. 2025
CITY ENGINEER: <i>Hae Won Ritchie</i>		DRAWN BY: JMH
APPROVED BY: R.C.E. C69532		ST-08
		DETAIL NO: